


## Maudo



Flamed Finish

### Description

|                      |   |
|----------------------|---|
| Appearance:          | Medium to coarse grained crystalline rock             |
| Finishes:            | Flamed, Fine Picked, Polished, Honed                  |
| Governing Standards: | Where applicable BS EN 1341/1342/1343 will be applied |
| Quarry of Origin:    | Binh Dinh Province, Vietnam                           |

### Physical Properties

|                           |                             |
|---------------------------|-----------------------------|
| Work Dimensions:          | To Customer's specification |
| Tolerances on Dimensions: | Class 2                     |
| Abrasions Resistance:     | 16.3mm                      |
| Compressive Strength:     | 153MPA                      |
| Flexural Strength:        | 19.9MPA                     |
| Material Density:         | 2610kg/m3 (typically)       |
| Slip Resistance:          | 66 - WET<br>89 - DRY        |
| Water Absorption:         | 0.22%                       |

### Supply

|             |   |
|-------------|---|
| Crate Size: | Maximum 1.8 tonnes, approximate size 1.0 x 1.0 x 0.80 high        |
| Packaging:  | Wooden crates, suitable for stacking & transportation by forklift |

### Cleaning & Maintenance

All stones vary and each one should be looked at on an individual basis. Many are slightly alkali so acid cleaners should be avoided. For more information, please contact our technical department.